

# CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

## MODEL L-69-57D

PORTABLE LOAD BANK

The **L-69-57D LOAD BANK** is designed to provide a temporary load for field servicing and testing 480VAC and 208VAC three phase, 60HZ generators and inverters. The L-69-57 load bank is air cooled. A 120VAC outlet is required to operate the fans and relays. The load is 57KW at 480VAC and 240 three phase. At 208VAC the unit will pull a load 45KW. This unit will also test 120VAC & 240VAC single phase.

### MODEL L-69-57D DIMENSIONS

Length.....22"  
Width.....8"  
Height.....21"  
Weight.....60 lbs.



### FEATURES

- Load steps: 1, 2, 2, 5, 10, 12.5, 25 KW on three phase 480VAC and 240VAC
- Load steps: .8, 1.6, 1.6, 4, 8, 9.7, 19.3 KW on three phase 208VAC
- Load steps: 500W, 1KW, 1KW, 2.5KW, 5KW, 6.25KW, 12.5KW on single phase 240VAC
- Load steps: 130W, 250W, 250W, 630W, 1.25 KW, 1.5KW, 3KW on single phase 120VAC
- Tests 240VAC three phase, 240VAC single phase and 120VAC single phase
- Plug test pins for connecting test leads
- Cm-Lok Connectors with 10ft cable
- Meters: Digital Multimeter
- Power indicator lights
- Thermal protection
- Carrying case

**WEBSITE: [www.cannonloadbanks.com](http://www.cannonloadbanks.com)**